

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
28 December 2000 (28.12.2000)

PCT

(10) International Publication Number
WO 00/79328 A1

- (51) International Patent Classification⁷: G02B 27/14 (74) Agents: HJORTH, Beverly, E. et al.; Weingarten, Schur-
gin, Gagnebin & Hayes LLP, Ten Post Office Square,
Boston, MA 02109 (US).
- (21) International Application Number: PCT/US00/14712
- (22) International Filing Date: 30 May 2000 (30.05.2000) (81) Designated States (national): CA, JP.
- (25) Filing Language: English (84) Designated States (regional): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE).
- (26) Publication Language: English
- (30) Priority Data: 60/140,327 21 June 1999 (21.06.1999) US
Published:
— With international search report.
- (71) Applicant: THE MICROOPTICAL CORPORATION
[US/US]; 33 Southwest Park, Westwood, MA 02090 (US).
For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.
- (72) Inventors: SPITZER, Mark, B.; 5 Mink Trap Lane,
Sharon, MA 02067 (US). CRAWFORD, John, O.; 11
Donna Pass, Hopkinton, MA 01748 (US).

(54) Title: ILLUMINATION SYSTEMS FOR EYEGLASS AND FACEMASK DISPLAY SYSTEMS



(57) Abstract: A display illumination and viewing system (figure 4) has an illumination optical path and a viewing optical path coinciding along a portion of their lengths. A display (60) is located at one end of the coinciding path portion. A first lens system is located on the coinciding path portion and a second lens system is located on the viewing optical path. An illumination assembly is located on the illumination optical path and off the coinciding path portion. The illumination assembly is spaced from the first lens system by a distance corresponding to a focal length of the first lens system. A reflective and transmissive element is located at an opposite end of the coinciding path portion to reflect light from the illumination assembly onto the coinciding path portion toward the display and to transmit light from the display along the viewing optical path. In another aspect of the invention, the image display system is operable in a color

mode and a monochrome mode. Illumination circuitry (figures 8-11) is in communication with an illumination source and includes a switch operative to switch the illumination source between the color mode to provide a color display and the monochrome mode to provide a monochrome display.

-1-

TITLE OF THE INVENTION

Illumination Systems For Eyeglass and
Facemask Display Systems

5 CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the benefit under 35 U.S.C.
§ 112(e) of U.S. Provisional Application No. 60/140,327,
filed June 21, 1999, the entire disclosure of which is
incorporated herein by reference.

10

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR
DEVELOPMENT

The development of this invention was supported by
R&D Contract DAAN02-98-C-4026. The U.S. government may
15 have certain rights in this invention.

BACKGROUND OF THE INVENTION

Miniature active matrix liquid crystal displays
(AMLCD) require an illumination source. In systems using
20 transmissive AMLCDs, a light source is placed behind the
display. Fig. 1 shows a simple prior art approach in
which a transmissive AMLCD 10 is provided with an light
emitting diode (LED) backlight 20. Rays from the
backlight 30 propagate through the AMLCD and are
25 modulated to produce an image. In some AMLCDs, color is
obtained by sequentially loading red, green, and blue
subframes into the AMLCD, and by simultaneously
sequentially illuminating red, green, and blue LEDs.
Sequential illumination is accomplished by providing
30 current sequentially through one of the desired LED
leads 40. A beam shaping element 50, such as a Fresnel
lens, may be used to collimate the light. Other

-2-

elements, such as diffusers or filters, may also be employed. AMLCDs and illuminators of this type are available commercially from Kopin Corporation. The viewing system for such displays may comprise simple optical magnifier optics, or a multi-stage optical system characterized by intermediate image planes between the stages.

Prior art miniature reflective AMLCDs (Fig. 2) use an illuminating system that is based on a beam splitter cube 70 adjacent to the display 60. The beam splitter may comprise a polarization splitting coating 71 which serves to linearly polarize the illuminating light, and which also acts as the analyzer for the LCD. The polarizing beam splitter may alternatively be formed from polymer films. As with the transmissive AMLCD, optical elements 50 may be used to collimate, diffuse or filter the illumination.

Fig. 3 shows a more complex prior art reflective AMLCD system that includes a compact, simple magnifier added to the illuminator system for viewing a magnified image of the display 60 (U.S. Patent 5,596,451). In this prior art device, a compact system is formed by using a single beam splitter 71 for illuminating and viewing the image from the AMLCD 60. Although the beam splitter 71 is used for illumination and for viewing, mirror 42, which provides the magnification, is not employed in the illumination system optical path. A lens or mirror to affect vergence of the illumination light is not needed because the light source 34 in this design is a broad area emitter.

For the case of reflective AMCLDs, projection systems have been described that employ efficient

-3-

illuminators, based on lamps and collimating optics. Collimating optics provide efficient, uniform illumination of the reflective display (see, for example, U.S. Patent No. 6,036,318). Collimation systems of this type are not employed in head-mounted displays owing to high weight and volume that results from the additional lenses and path length needed.

Collimating illumination optics are generally used in projection systems that employ high intensity lamps and projection lens systems, such as disclosed in U.S. Patent No. 5,949,503. In some cases, such as in the patent cited, a portion of the projection optics may be used for illumination. For projection systems, this approach leads to improved illumination uniformity and improved contrast in the projected image.

SUMMARY OF THE INVENTION

This invention relates to the attainment of an improved illuminating system for reflective liquid crystal displays. The improvement is based on integrating the illumination system with the magnifying system and thus using a single set of optical elements for the two purposes of magnifying the image and illuminating the display. The invention also relates to a system for obtaining high brightness monochrome images which may be applied to reflective or transmissive liquid crystal displays.

More particularly, the invention provides a display illumination and viewing system comprising an illumination optical path and a viewing optical path. At least a portion of the illumination optical path coincides with at least a portion of the viewing optical

-4-

path to form a coinciding path portion. A display comprising an active matrix liquid crystal display is located at one end of the coinciding path portion. A first lens system is located on the coinciding path portion and provides an image plane on the viewing optical path. A second lens system is located on the viewing optical path.

An illumination assembly, such as red, green, and blue LEDs, is located on the illumination optical path and off the coinciding path portion. The illumination assembly is spaced from the first lens system by a distance corresponding to the focal length of the first lens system. A reflective and transmissive element, such as a beam splitter, is located at an opposite end of the coinciding path portion to reflect light from the illumination assembly onto the coinciding path portion toward the display and to transmit light from the display along the viewing optical path. In this manner, the present invention provides a collimating illumination system for a head-mounted reflective AMLCD, offering uniform and efficient illumination, with less weight and volume than prior art systems.

In another aspect of the invention, the image display system is operable in a color mode and a monochrome mode. The display system comprises an active matrix liquid crystal display operable at a determined frame rate comprising sequential loading of red, green, and blue subframes. An illumination source comprising red, green, and blue light sources, such as LEDs, is disposed to illuminate the active matrix liquid crystal display. Illumination circuitry is provided in communication with the illumination source and includes

-5-

a switch operative to switch the illumination source between the color mode to provide a color display and the monochrome mode to provide a monochrome display. In this manner, the present invention obtains increased
5 brightness by providing the ability to switch the illuminator to a monochrome mode. In a further aspect, the invention also provides for adjusting illuminator brightness.

10 DESCRIPTION OF THE DRAWINGS

The invention will be more fully understood from the following detailed description taken in conjunction with the accompanying drawings in which:

Fig. 1 is a schematic illustration of a prior art
15 transmissive active matrix liquid crystal display illumination system;

Fig. 2 is a schematic illustration of a prior art reflective active matrix liquid crystal display illumination system;

20 Fig. 3 is a schematic illustration of a prior art reflective active matrix liquid crystal display illumination system with magnifier;

Fig. 4 is a display system incorporating an illumination system and a viewing system;

25 Figs. 5a and 5b are schematic illustrations of the optical principals of a display system according to the present invention;

Fig. 6 is a schematic illustration of an optical design of the display system of Figs. 5a and 5b;

30 Fig. 7 is a schematic illustration of a display system according to the present invention in use with an eyeglass display;

-6-

Fig. 8 is a block diagram and circuitry of an illumination control system according to the present invention;

5 Fig. 9 is a block diagram and circuitry of a further embodiment of an illumination control system according to the present invention;

Fig. 10 is a block diagram and circuitry of a still further embodiment of an illumination control system according to the present invention; and

10 Fig. 11 is a block diagram and circuitry of a still further embodiment of an illumination control system according to the present invention.

DESCRIPTION OF THE INVENTION

15 This invention comprises the integration of the viewing optics and the illumination optics in a single or multi-stage optical system. By integration we mean that some of the optical elements affecting vergence of rays that are used for the viewing optics also serve to
20 collimate the light in the illumination system, thereby lowering cost, weight and volume.

By way of preliminary explanation of the present invention, Fig. 4 illustrates a display system based on using the prior art collimation system shown in Fig. 2.
25 An illumination system 22 is coupled with a viewing system 23 to provide an image to a viewer. The illumination system comprises red 53, green 54, and blue 55 LEDs, an optional diffuser 49, a Fresnel lens 50, and a polarization beam splitter 71. Illumination from the
30 LEDs passes through the diffuser if employed, and is collimated by the Fresnel lens 50 to uniformly illuminate the AMLCD 60. Light of the reflected

-7-

polarization is directed to the AMLCD by the beam splitter 71. The AMLCD rotates the polarization of the light at each of its pixels to an angle in accordance with electrical signals representing the image. Rays
5 pass from the illumination stage 22 to the magnification stage 23, and are then viewed through the lenses 150 and 160. Any number of optical surfaces may be used to magnify the image and to correct aberrations; for simplicity we have represented the lens surfaces by the
10 singlet lenses 150 and 160. In practice, these lenses 150, 160 may each be achromatic doublet or triplet lenses, aspheres, or more complex combinations of surfaces.

Figs. 5a and 5b illustrate the optical principal of
15 this invention. A reflective AMLCD 60 is viewed through a lens system that has two stages of magnification, represented by lens system 150 and lens system 160. A viewing path is defined from the AMLCD 60 through the lens system 150 and lens system 160 to a user's eye.
20 Each lens system is characterized by a focal length, f . Referring to Fig. 5a, in accordance with Newton's lens equation ($N \cdot P = f_1 \cdot f_2$), lens system 150 forms an intermediate image plane as shown between 150 and 160; the position of this plane is given by Newton's lens
25 equation or its equivalents, which are well known in the art. If lens system 160 is placed at a distance from the image plane equal to its focal length, the user perceives an image at infinity. The position of lens 160 may be varied to change the distance of the virtual
30 image. The magnification of the system is given by the product of the magnification of the two stages, as is well known in the art.

-8-

Figs. 5a and 5b also show the insertion of a reflective and transmissive element, for example, a beam splitter 200 in between lens systems 150 and 160. The beam splitter may be a polarization beam splitter made by vacuum deposition of thin film multilayers as is known in the art, or made by polymer techniques (such products are offered by 3M for example), or it may be a vacuum-deposited thin metal film with approximately 50% transmission (a half silvered mirror). Alternatively, a polarization beam splitting cube may be used. Referring to Fig. 5b, it can be seen that the purpose of the beam splitter 200 is to reflect light from an illumination source, such as LED lamp 100, which may be a multi-color lamp comprising red, green and blue LEDs used in field sequential color illuminators, into the optical path. The path between the LED lamp 100 and the AMLCD 60 defines an illumination path. It can be seen that the illumination path coincides with a portion of the viewing path. If the LED is placed at a distance from lens system 150 equal to the focal length f_2 of lens system 150 (shown as the distance $a+b$ in Fig. 5b), then 150 acts to collimate the light and thus improves the uniformity of the illumination on the AMLCD 60. Diffusers and other optical elements may be used between the LED and the beam splitter to homogenize the light incident on the AMLCD or to develop an extended light source in accordance with the viewing requirements of the complete system.

Fig. 6 illustrates an example of an optical design based on this principal. The lens surfaces 150, 160 are aspheres known in the art and represented by the equation:

-9-

$$z: = \frac{cr^2}{1+\sqrt{1-(1+k)\cdot c^2\cdot r^2}} + \alpha_2\cdot r^4 + \alpha_3\cdot r^6 + \alpha_4\cdot r^8$$

5

with coefficients as given in Table 1. Table 2 summarizes the optical prescription for the imaging path (between display 60 and the eye pupil), and Table 3 summarizes the prescription for the illumination path (between lamp 100 and the display 60).

10

Table 1. Asphere Coefficients

Coefficient	Value
k	0
α_2	$-0.1304 \times 10^{-2} \text{ mm}^{-3}$
α_3	$7.2502 \times 10^{-6} \text{ mm}^{-5}$
α_4	$-8.3167 \times 10^{-7} \text{ mm}^{-7}$

15

Table 2. Optical Prescription for the Imaging Path

Description	Radius (mm)	Material	Thickness (mm)	Notes
Eye Pupil	Infinity	Air	25	Eye Relief
Eye Lens 1st Surf	13.2	BK7	5	Planoconvex Lens
Eye Lens 2nd Surf	Infinity	BK7	6	Bonded to Prism
Mirror Surf	Infinity	BK7	25.44	
Internal Image	Infinity	BK7	25	End of Prism
Lens Air Space	Infinity	Air	2	Air Space
Relay Lens 1st Surface (Dual Use see Table 3)	5.9	BK7	4	CV, Lens could be Plastic
Relay Lens 2nd Surface	147.0562 at Vertex $c=1/R$	Air	25.98	CC, Asphere as per Table 1
Display	Infinity			Cover glass Omitted

Note: User image at 609 mm.

-10-

Table 3. Optical Prescription for the Illumination Path

Description	Radius (mm)	Material	Thickness (mm)	Notes
Illuminator and Air Space	Infinity	BK7	0.6	Mount to Prism
Partial Reflection Surf	Infinity	BK7	6	Polarization Beam Splitter
Internal Reflection	Infinity	BK7	6	To End of Prism
Lens Air Space	Infinity	Air	2	Air Space
Collimator Lens 1st Surf. (Dual Use see Table 2)	5.9	BK7	4	CV, Lens could be Plastic
Collimator Lens 2nd Surf.	147.0562 at Vertex $c=1/R$	Air	25.98	CC, Asphere, Table 1
Display	Inf			Cover glass omitted

In these designs, reduced weight is attained by eliminating the need for a separate lens for collimating light from the LEDs. Referring to Fig. 4, it can be seen that by eliminating the collimating lens 50 (shown in Fig. 4), and the required distances associated with its focal length, a reduction in size and weight is attained.

Fig. 7 illustrates how the invention can be used in an eyeglass display of the type described in U.S. Patent 5,886,822. A housing 170 for a reflective display 60 and magnifying lens system 150 is placed in proximity to an eyeglass lens 210. The display 60 is illuminated by a light source 100. Lens system 150 projects an image plane at the entrance pupil of the optical system in lens 210. Lens 210, with a magnifying internal optical relay formed by lens 220, polarization beam splitter 240, quarter wave plate 260, and concave mirror 250 provide an image to the eye of the user which is perceived as originating in front of the lens 210 at a comfortable distance.

-11-

In the foregoing discussion, we have referred to the image source as an LED or array of LEDs, since LEDs are a common light source in these displays. Many alternative illumination sources may be used, including
5 lasers, an optical fiber delivering light from a remote source, or other lamps.

The use of sequential red, green, blue illumination in an eyeglass system of the type shown in Fig. 7 provides an image of excellent color. Sequential
10 lighting of the LEDs however, reduces the duty cycle of the LEDs and therefore reduces the total amount of light provided to the eye. In systems of the type shown in Fig. 7, in which a beam splitter 240 is used as a combiner to fuse the ambient scene and the rays from the
15 display, the viewer may require an unusually bright image, such as when in bright ambient sunlight.

Many applications such as the eyewear display previously cited require a color display for certain images, and a high brightness display for other images
20 viewed in high ambient lighting, which may not need color. To make the sequential color display very bright, this invention also includes a method for implementing a high brightness monochrome mode, which involves powering the red, green, and blue LEDs simultaneously at up to
25 100% duty cycle.

In one embodiment of this invention shown in Fig. 8, the LEDs 301, 302, 303 are turned on continuously without any change to the frame rate of the AMLCD using switch 300. Continuous and simultaneous illumination of
30 all three LEDs results in the portrayal of the image as black and white, and with the white being much brighter

-12-

than any color that would be developed from sequential LED flashes of red, green, and blue.

Simultaneous illumination can be attained by employing a switch 300, as shown in Fig. 8 applied to the illuminator power circuit. In one position of the switch, the LEDs are connected to the sequential color drive circuit in the backlight controller. In the other position, the LEDs are connected to a current source. Fig. 8 shows the current source comprising V_{DD} , the LEDs 301, 302, 303, current-limiting series resistors 311, 312, 313, and ground; however, other circuits may be used to provide current to the LEDs. The switch 300 provides current to the LEDs continuously and simultaneously, so that at least triple the duty cycle for each LED is obtained. The technique may be applied to transmissive AMLCD illuminators (Fig. 1) or to reflective AMLCD illuminators (Fig. 2).

An alternative embodiment is shown in Fig. 9. A switch 350 is used to provide a logic input to the display controller 330 to control the LEDs. The display controller 330 supplies illumination signals along paths 319 to the LEDs through OR gates 304, 305 and 306. Logic output from the OR gates is applied to the gates of the control transistors 307, 308, 309 which enables current to flow through the LEDs in correspondence with the logic signal supplied on the paths 319. The switch 350 is used to select the operating mode of the illuminator. In the left position (ground), the inputs of the OR gates are held to ground, allowing the control signals on paths 319 to have full authority over the control of the LEDs. In the center position, the OR gate inputs 321, 322, and 323 are held at V_{DD} meaning that the output

-13-

of the OR gates is held high, and the LEDs are consequently continuously illuminated, regardless of the signals on paths 319. If switch 350 is in the far right position, the lines 321, 322, 323 are held at a value
5 established by the logic within the display controller, or by an alternative logic path (not shown) from another control circuit.

A third embodiment (Fig. 10) comprises a switch 310 that also provides a logic signal path 320 to the AMLCD
10 display controller. The logic signal on line 320 signifies the selection by the user of the high brightness monochrome mode. This signal enables the controller logic to reduce power consumption in memory and elsewhere and to adjust the signal to use the
15 optimal balance of red, green, and blue information from which to construct a monochrome image.

A further improvement to this invention comprises a circuit that allows the microprocessor to select the background color. Ordinarily, by running red, green, and
20 blue LEDs at full brightness, one obtains a high brightness black and white display, as previously described. By controlling the balance of current among the three LEDs, any backlight color may be attained. Black and white may be used as the primary high
25 brightness illumination, but if the application running on the computer so selects, the background color can be switched to, for example, red to indicate a warning in black and red. This is obtained by powering only the red LED.

30 Note that the LEDs do not have to be illuminated continuously in monochrome mode, or for their full duty cycle in color mode. The logic devices described above

-14-

can be used to provide reduced duty cycles to affect reduced brightness in either monochrome or color mode. Fig. 12 shows a diagram of how such brightness control can be attained. The signal to illuminate one of the LEDs originates at the display controller 330. A pulse is provided simultaneously to a one shot multivibrator 400 by path 451. The signal to illuminate LED 303, for example, passes from the display controller 330 through the OR gate 306 and is passed to an AND gate 403. The AND gate, passes the illumination signal only for the time that the pulse 420 is present. This pulse 420 is initiated by multivibrator 400 upon receipt of the initiating pulse from line 451. The duration of the pulse is controlled by the setting of the potentiometer 410, under the control of the user of the system. If the pulse width time is t , the corresponding AND gate is held open for a corresponding time, t , and the LED is illuminated for the time t . Thus, the width of the pulse from multivibrator 400 exerts control over the duty cycle of the LEDs and hence brightness. Fig. 11 shows that the signal from the AND gate passes through a series resistor 413 which controls the current through the matched pair of field effect transistors 460. Note that the pulse width, t , may also be controlled by logic signals that can be applied by the display controller, or that can be applied to the one-shot multivibrator through an additional logic path (not shown).

The illumination circuits shown in Figs. 8 through 12 may be implemented in discrete logic devices, in a programmable logic device, or in a custom integrated circuit. Alternatively, the circuits may also be integrated within the display controller. The circuits

-15-

may be configured to control alternative illumination sources such as laser diodes.

The invention is not to be limited by what has been particularly shown and described, except as indicated by
5 the appended claims.

-16-

CLAIMS

What is claimed is:

5

1. A display illumination and viewing system comprising:

an illumination optical path and a viewing optical path, at least a portion of the illumination optical path coinciding with at least a portion of the viewing optical path to form a coinciding path portion;

10

a display comprising an active matrix liquid crystal display located at one end of the coinciding path portion;

15

a first lens system located on the coinciding path portion and having a first focal length, the first lens system providing an image plane on the viewing optical path;

a second lens system located on the viewing optical path;

20

an illumination assembly located on the illumination optical path and off the coinciding path portion, the illumination assembly spaced from the first lens system by a distance corresponding to the first focal length of the first lens system; and

25

a reflective and transmissive element located at an opposite end of the coinciding path portion to reflect light from the illumination assembly onto the coinciding path portion toward the display and to transmit light from the display along the viewing optical path.

30

-17-

2. The display illumination and viewing system of claim 1, wherein the illumination assembly comprises red, green, and blue light emitting diodes.

5 3. The display illumination and viewing system of claim 1, wherein the illumination assembly comprises red, green, and blue laser diodes.

10 4. The display illumination and viewing system of claim 1, further comprising a further optical element on the illumination optical path.

15 5. The display illumination and viewing system of claim 4, wherein the further optical element comprises a diffuser.

20 6. The display illumination and viewing system of claim 1, wherein the reflective and transmissive element comprises a beam splitter.

7. The display illumination and viewing system of claim 6, wherein the beam splitter comprises a polarization beam splitter.

25 8. The display illumination and viewing system of claim 6, wherein beam splitter comprises thin film multilayers or a thin film metal layer or a half silvered mirror or a beam splitting cube.

30 9. The display illumination and viewing system of claim 1, further comprising a housing, the display, the first lens system, the illumination assembly, and the

-18-

reflective and transmissive element supported within the housing.

10. An eyewear assembly comprising:

5 a head-mountable frame;

an eyewear lens supported by the frame in front of a user's eye; and

the display illumination and viewing system of claim 1 disposed to transmit light along the viewing optical path into an optical path through the lens.

11. The eyewear assembly of claim 10, further comprising a housing supported on the head-mountable frame, the display, the first lens system, the illumination assembly, and the reflective and transmissive element supported by the housing; and wherein the second lens system is affixed to the eyewear lens.

12. An image display system operable in a color mode and a monochrome mode, comprising:

an active matrix liquid crystal display operable at a determined frame rate comprising sequential loading of red, green, and blue subframes;

25 an illumination source comprising red, green, and blue light sources disposed to illuminate the active matrix liquid crystal display; and

illumination circuitry in communication with the illumination source and including a switch operative to switch the illumination source between the color mode to provide a color display and the monochrome mode to provide a monochrome display.

-19-

13. The image display system of claim 12, wherein the illumination circuitry is operative in the color mode to drive the red, green, and blue light sources sequentially in synchronization with the sequential
5 loading of the red, green, and blue subframes.

14. The image display system of claim 12, further comprising a backlight controller and wherein in the color mode, the illumination circuitry is in
10 communication with the backlight controller.

15. The image display system of claim 12, wherein the illumination circuitry is operative in the monochrome mode to drive the red, green, and blue light sources
15 simultaneously in synchronization with the sequential loading of the red, green, and blue subframes.

16. The image display system of claim 12, wherein the illumination circuitry is operative in the monochrome mode to connect the illumination source to a current
20 source.

17. The image display system of claim 12, wherein the illumination circuitry is operative in the monochrome mode to drive the red, green, and blue light sources
25 each at 100% duty cycle simultaneously.

18. The image display system of claim 12, wherein the illumination circuitry is operative in the monochrome mode to drive the red, green, and blue light sources
30 each at less than 100% duty cycle.

-20-

19. The image display system of claim 12, wherein the illumination circuitry further includes a multivibrator operative to provide a pulse of controlled duration to limit illumination time of the light sources.

5

20. The image display system of claim 12, wherein the illumination circuitry is operative in the monochrome mode to drive a single one of the red, green, and blue light sources at a time.

10

21. The image display system of claim 12, wherein the illumination circuitry is operative in the monochrome mode to drive a combination of red, green, and blue light sources, each with a current or duration selected to produce a monochrome background color.

15

22. The image display system of claim 12, further comprising a display controller in communication with the display.

20

23. The image display system of claim 22, wherein in the color mode, the illumination circuitry is in communication with the display controller.

25

24. The image display system of claim 22, wherein the switch is in communication with the display controller to receive a logic signal from the display controller.

30

25. The image display system of claim 22; wherein the switch is in communication with the display controller and the display controller is operative to control power consumption of the illumination source.

-21-

26. The image display system of claim 12, further comprising a display controller in communication with the display and the illumination circuitry, the illumination circuitry further including OR gates associated with each of the red, green, and blue light sources, the OR gates operative to receive a logic signal from the display controller and a logic signal from the switch.

27. The image display system of claim 12, wherein the switch is operable by a user to select the color mode or the monochrome mode.

28. The image display system of claim 12, wherein the display is a reflective active matrix liquid crystal display or a transmissive active matrix liquid crystal display.

29. An illumination circuit operative with the image display system of claim 12.

1/7




FIG. 2
PRIOR ART








FIG. 3
PRIOR ART




2/7

**FIG. 4**

3/7

**FIG. 5A****FIG. 5B**



4/7





3D LAYOUT
RAY TRACE

FIG. 6


5/7

**FIG. 7****FIG. 8**

6/7

**FIG. 9****FIG. 10**

7/7

**FIG. 11**

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US00/14712

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) :G02B 27/14

US CL :359/630; 345/7-9

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 359/630; 345/7-9

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

USPAT, JPO, EPO, Derwent

search terms: display, active adj3 matrix, liquid adj3 crystal, lcd, illuminat\$

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5,808,589 A (FERGASON) 15 September 1998 (15/09/98) all	1-29
A	US 5,626,410 A (CHAMBERS et al.) 06 May 1997 (06/05/97) all	1-26

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z

document member of the same patent family

Date of the actual completion of the international search

24 JULY 2000

Date of mailing of the international search report

03 AUG 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

RICKY MACK

Telephone No.

(703) 305-6984

Form PCT/ISA/210 (second sheet) (July 1998)*

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
28 December 2000 (28.12.2000)


PCT

(10) International Publication Number
WO 00/79328 A1

- (51) International Patent Classification⁷: G02B 27/14 (72) Inventors: SPITZER, Mark, B.; 5 Mink Trap Lane, Sharon, MA 02067 (US). CRAWFORD, John, O.; 11 Donna Pass, Hopkinton, MA 01748 (US).
- (21) International Application Number: PCT/US00/14712
- (22) International Filing Date: 30 May 2000 (30.05.2000) (74) Agents: HJORTH, Beverly, E. et al.; Weingarten, Schur-
gin, Gagnebin & Hayes LLP, Ten Post Office Square,
Boston, MA 02109 (US).
- (25) Filing Language: English
- (26) Publication Language: English
- (81) Designated States (national): CA, JP.
- (30) Priority Data: 60/140,327 21 June 1999 (21.06.1999) US (84) Designated States (regional): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE).
- (71) Applicant: THE MICROOPTICAL CORPORATION Published:
[US/US]; 33 Southwest Park, Westwood, MA 02090 (US). — With international search report.

[Continued on next page]

(54) Title: ILLUMINATION SYSTEMS FOR EYEGGLASS AND FACEMASK DISPLAY SYSTEMS



(57) Abstract: A display illumination and viewing system (figure 4) has an illumination optical path and a viewing optical path coinciding along a portion of their lengths. A display (60) is located at one end of the coinciding path portion. A first lens system is located on the coinciding path portion and a second lens system is located on the viewing optical path. An illumination assembly is located on the illumination optical path and off the coinciding path portion. The illumination assembly is spaced from the first lens system by a distance corresponding to a focal length of the first lens system. A reflective and transmissive element is located at an opposite end of the coinciding path portion to reflect light from the illumination assembly onto the coinciding path portion toward the display and to transmit light from the display along the viewing optical path. In another aspect of the invention, the image display system is operable in a color mode

and a monochrome mode. Illumination circuitry (figures 8-11) is in communication with an illumination source and includes a switch operative to switch the illumination source between the color mode to provide a color display and the monochrome mode to provide a monochrome display.



(48) Date of publication of this corrected version:

19 April 2001

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(15) Information about Correction:

see PCT Gazette No. 16/2001 of 19 April 2001, Section II